Anyline Web SDK Datasheet v51

Anyline Web SDK is based on JavaScript and designed to be integrated into websites or web apps. This flexibility enables end users to experience all the benefits of data capture without needing to install a dedicated app on their mobile device. Anyline Web SDK is built to handle all data processing on the user's device, making data capture possible without an internet connection.

Disclaimer

Anyline products are built to deliver fast and reliable data capture solutions. There are however, certain factors that can limit or negatively impact data capture speed and accuracy. These are factors for which we are not responsible and cannot assume any warranty or liability. These include, for example:

- Non-compliance with technical requirements for the specific product and/or module, as set forth in this Datasheet or otherwise agreed
- An unsuitable scanning environment, such as scanning an object under extreme lighting conditions or from a far distance
- Any obstructions on the object that you wish to scan, such as obscured text or a very shiny surface
- The quality of an image you try to scan, for example images that are blurry, out of focus or low resolution images
- Incorrect handling by users, such as using the products with a lack of sufficient experience or unsteady hands

Furthermore, each module is conceived for certain applications and has a specific set of features and capabilities. Please read the module sections carefully to understand for which use cases you can deploy modules and what the module can and cannot do. Any use of our products beyond such scope is something we do not warrant or assume any liability for.

Requirements

Web SDK		
Programming Language	JavaScript	
Recommended Browsers	Latest version of Chrome, Safari, Firefox	
Camera Resolution	Minimum: 720p video camera	
	Recommended: 1080p video camera	
SDK Size*	50 MB	

^{*}Actual numbers may vary depending on the platform, operating system and or recognition task

Modules Overview

Anyline Web SDK contains a number of modules designed for capturing data from a range of different objects.

	Web SDK
Tire DOT/TIN	•
Tire Size	•
Tire Commercial ID	•
Licence Plate (Europe and US)	•
VIN	•
Meter	•
Meter Serial Number	•
Barcode	•
ID (Germany and Austria)	•
MRZ	•
Container	•
Custom Serial Number	•

Tire DOT/TIN

Capabilities **Specifications** • Tire Identification Numbers with and without DOT • Universal TIN mode: prefix • Scans with or without DOT prefix o Allowed characters: A-Z, 0-9 o Length: between 6 and 17 characters • The last 4 characters must be digits and have to represent a valid production date (WWYY) • DOT mode: o Scans only with DOT prefix $\circ~$ Only tires produced after the year 2000 are scannable • Allowed characters: A-Z (excluding letters O, G, I, Q, S, Z), 0-9 o Length: between 6 and 17 characters including DOT • The last 4 characters must be digits and have to represent a valid production date (WWYY)

Tire Size

<u>Capabilities</u>	<u>Specifications</u>
---------------------	-----------------------

- Tire specifications including: tire width, tire
 aspect ratio in millimetres, rim diameter in inches,
 load index (single or double), extra load rated
 tire, speed rating, fabric carcass construction,
 commercial tire designation, mud and snow
 winter tire, vehicle type recognition
- Allowed characters: A-Z (excluding letters O and I), 0-9, /+-&()
- Length: Up to 20 characters (single line only)
- Supported formats () = optional:
 - (X)000/00(X)X0000(0)X
 - (X)000/00(X)X00(X)
 - o (X)000/00X00X(0)00/(0)00X

Tire Commercial ID

Manufacturer's ID code from Michelin,
 Continental, Goodyear, Pirelli/Prometeon,
 Bridgestone, CEAT, Salva (and more) tires on trucks, buses or trailers.

Specifications

- Allowed characters: A-Z (excluding letter O), 0-9
- Length: 7 14 characters (single line only)
- Regular expression: [0-9A-NP-Z]{3}[0-9]
 {4,10}[0-9A-NP-Z]{0,1}

License Plate

Capabilities

- All EU countries + Albania, Andorra, Armenia, Azerbaijan, Belarus, Bosnia-Herzegovina, Faroe Islands, Georgia, Gibraltar, Iceland, Kosovo, Liechtenstein, Macedonia, Moldova, Monaco, Montenegro, North Macedonia, Norway, Russia, Serbia, Switzerland, Turkey, Ukraine and United Kingdom
- All US states + American Samoa, District of Columbia, Guam and Puerto Rico

Specifications

- Allowed characters: A-Z (excluding letter O), 0-9
- Length: 7 14 characters
- Limited support for two-line license plates for the following countries: Belarus, Belgium, Bulgaria, Croatia, Denmark, Estonia, Finland, Hungary, Latvia, North Macedonia and Romania
- No support for multi-line US plates
- Limited support for small two-line plates on light motorised vehicles such as mopeds
- State detection is not reliable for US vanity plates

Vehicle ID Number (VIN)

Capabilities

 Vehicle Identification Numbers 17 characters in length according to ISO 3779

Specifications

Meter

Capabilities

- Analog Meters: Gas, Electric, Water
- Digital Meters: Gas, Electric, Water, dot matrix display
- Selected Meter Types: A49U, C114U, C14U11, G1X4, W6060, MM2600F3, CM160J, CL204,

Specifications

 Analog Meters: 4-10 pre-decimal digits, up to 3 decimal digits (Gas, Electric, Water), black
 red, metallic and white backgrounds

- ML262XF6, ML242XF6, C114U, G1Y6U, 7AA3061, 7CA5461, 7AA5041, 7CA5061-7
- Selected Meter Brands: AEG, Danubia DZG, Landis + Gyr, Reimer & Seidl, Schlumberger AEG, Schlumberger Danubia, Siemens, Uher
- Digital Meters: 7-segment display with at least 3 digits, 4-6 pre-decimal digits, up to 3 decimal digits (Heat)

Meter Serial Number

Capabilities

 Serial numbers for a wide range of meter types and brands

Specifications

• Uppercase alphanumeric codes

Barcode

Capabilities

- 1D Barcodes: Bookland EAN, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, Databar, Databar Expanded, Discrete 2 of 5, EAN-8/JAN 8, EAN-13/JAN 13, EAN-14, EAN 18, EAN-99, GS1-128, GS1 Databar, Identcode, Inverse 1D, ISBN-10, ISBN-13, ISBT 128, ISMN, ISNN, ISSN EAN, Interleaved 2 of 5 (ITF), ITF-14, Leitcode, Matrix 2 of 5, MSI, RSS 14, RSS Expanded, Trioptic Code 39, UCC Coupon Code, UPC-A, UPC-E
- 2D Barcodes: Aztec, Aztec Inverse, Aztec vCard, Data Matrix, Data Matrix Inverse, DotCode, GS1 QR Code, Maxicode, Micro QR Code, QR Code, QR Inverse
- Stacked Linear Codes: PDF 417, Micro PDF417

Specifications

ID

Capabilities

• ID Card: Germany

• Driver's License: Austria, Germany

Specifications

• ID scanning supports Latin script

MRZ

Capabilities

 ID documents containing a Machine Readable Zone (MRZ)

Specifications

- TD3 booklet size passport (2 lines of 44 characters each)
- TD2 ID (2 lines of 36 characters each)

• TD1 credit card size ID (3 lines of 30 characters
each)
MRV-A Visa, MRV-B Visa according to ICAO
Document 9303 standard
Swiss Drivers License (1 line of 9 characters and
2 lines of 30 characters each)
LIS Green Card (3 lines of 30 characters each)

Container

Capabilities

• BIC-Codes (ISO 6346) and ILU-Codes (DIN EN 13044-1)

Specifications

- ILU-Codes and BIC-Codes in one or two horizontal lines
- BIC-Codes (ISO 6346) in one vertical line